WR4U 410 NE

NEAR EDGE WAX/RESIN

This High Speed Premium Wax/Resin on 4µm film is designed for high economic use on near edge printers. A ribbon you can rely on for the future of inline and packaging printing and the benefit 4U: great overall cost savings!

WAX | WAX-RESIN | RESIN | **W-R NEAR-EDGE** | R NEAR-EDGE

WR4U 410 NE

PRODUCT SUMMARY

- Good resistance to high temperature, exposure to UV light and chemicals
- Antistatic back coat and low print energy for print-head protection
- Superior printing quality at high speed on wide range of label stocks
- Excellent scratch and smudge resistance

TECHNICAL SPECIFICATIONS

PET film thickness	4,0 microns
Total ribbon thickness	6,6 microns
Transmissional density	1,8 MacBeth Scale
Ink melting point	72 ℃ / 161℉
Recommended max. print speed	600 mm / second up to 1.000 mm / sec.
Recommended media	Vellum, uncoated, semi gloss, tag board, matt/gloss coated PE, PET, PP, PVC

CHARACTERISTICS

Scratch resistance	●●●●●
Smudge resistance	●●●●●
Sensitivity	●●●●●
Rotated barcode sharpness	●●●●○
Fine line printability	●●●●○

APPLICATIONS

- Flexible packaging
- Food contact
- Cosmetics
- Outdoor
- Automotive

COMPLIANCE

- ISEGA
- REACH – SVHC Free
- RoHS/WEEE
- TSCA
- Additional regulatory requirements upon request

TTR Euroworks for you!

Edisonweg 47
2952 AD Alblasserdam
The Netherlands

+31 (0) 78 693 2000
sales@ttr.nl
www.ttr.nl