

THE TTR EUROWORKS 4U PRODUCT RANGE WORKS FOR YOU!

# R4U 610 NE

## STANDARD RESIN

High quality resin grade particularly designed for high heat resistance. The high density prints show excellent scratch and smudge resistance. Also excellent resistance to multiple chemicals. Low friction and anti-static back coat for printhead protection.

WAX

WAX-RESIN

RESIN

W-R NEAR EDGE

R NEAR EDGE

R4U 610 NE

## PRODUCT SUMMARY

- ✓ Very good resistance to high temperature
- ✓ Excellent scratch and smudge resistance
- ✓ Superb printing quality at medium speed
- ✓ Extreme abrasion resistance
- ✓ Excellent resistance to various chemicals


## TECHNICAL SPECIFICATIONS

PET film thickness	4,5 microns
Total ribbon thickness	7,1 microns
Transmissional density	1,65 MacBeth Scale
Ink melting point	80 °C / 158 °F
Recommended max. print speed	400 mm / second
Recommended media	PE, PP, PET, PVC, Metalised foil

## CHARACTERISTICS

Scrath resistance	✓✓✓✓✓
Smudge resistance	✓✓✓✓✓
Sensitivity	✓✓✓✓○
Rotated barcode sharpness	✓✓✓✓○
Fine line printability	✓✓✓✓○

## APPLICATIONS



## COMPLIANCE

- ✓ TSCA
- ✓ REACH - SVHC Free
- ✓ RoHS/WEEE
- ✓ Additional regulatory requirements upon request