

THE TTR EUROWORKS 4U PRODUCT RANGE WORKS FOR YOU!

WR4U 460 NE

WAX/RESIN NEAR EDGE

WR4U 460 NE Wax/Resin is an exclusive formulation for Near Edge printers. Its printing performance (speed, sensibility, versatility, blackness) gives unique possibilities for a large number of flexpack applications.

| WAX | WAX-RESIN | RESIN | W-R NEAR EDGE | R NEAR EDGE |
|-------------|-------------|-------------|---------------|--------------------|
| WR4U 400 NE | WR4U 410 NE | WR4U 420 NE | WR4U 430 NE | WR4U 460 NE |

PRODUCT SUMMARY

- ✓ Excellent printing quality at high speed
- ✓ Low print energy for print head protection
- ✓ Good resistance to high temperature and exposure to UV light

TECHNICAL SPECIFICATIONS

| | |
|-----------------------------|---|
| PET film thickness | 4,5 microns |
| Total ribbon thickness | 7,0 microns |
| Transmissional density | 1,7 MacBeth Scale |
| Ink melting point | 60°C / 135 °F |
| Recommended max. printspeed | 900 mm / second |
| Recommended media | Coated tags & labels, polyolefin, polyester, polypropylene and polyethylene films |

CHARACTERISTICS

| | |
|---------------------------|-------|
| Scratch resistance | ✓✓✓✓○ |
| Smudge resistance | ✓✓✓✓○ |
| Sensitivity | ✓✓✓✓✓ |
| Rotated barcode sharpness | ✓✓✓✓○ |
| Fine line printability | ✓✓✓✓✓ |

APPLICATIONS



COMPLIANCE

- ✓ ISEGA
- ✓ REACH - SVHC Free
- ✓ RoHS/WEEE
- ✓ TSCA
- ✓ Additional regulatory requirements upon request