

# iX4 Battle Card



## Product Pitch

iX4 series supports a large 8.26 inch outer diameter label roll and up to 450 meter ribbon capacity. Featuring 8 ips print speed, even print with the highest speed, it can still maintain the perfect print quality. Easily prints 10, 000 labels a day.

## Quick Specs

Print resolution: 203dpi and 300dpi  
Print Method: T/T or D/T  
Print Speed up to 8ips  
Maximum Print width 4.13"

## Optional Accessories


- Optional connectivity: WiFi 802.11 b/g/n module.
- Guillotine cutter/Rotary cutter: separate individual prints or batches of labels and tags.
- Peeler and internal rewinder: remove the liner paper to grab and apply labels quickly.
- Parallel cable/module.
- GPIO board module.

## Common vertical applications


- Manufacturing: product marking, compliance labeling, work in process labeling.
- Transportation and Logistics: shipping/receiving labeling, parcel routing, cross-docking.
- Retail: product labeling, event ticketing, packing slips.

## Features & Benefits


- Enlarged push button switches make it convenient for users who wear gloves.
- Dual USB host support printer stand-alone mode by plug-in scanner and/or keyboard for multiple data entry, increase printer usability with more input devices.
- New media calibration: Intelli mode & Smart mode calibration performing tasks immediately after installation.
- iLabelPrint APP supports mobile printing demands when using Argox printer connecting with mobile device such as smart phone, laptop computer or tablet. Both iOS and Android are supported.
- Printer tool supports web management and SNMP.




continuous



blackline



gap



notch

## Competitive advantages

		ARGOX iX4-250	BIXOLON XT2-40	GODEX ZX420i	TSC ML240P	ZEBRA ZT230
Model		203 dpi / 4"	203 dpi / 4"	203 dpi / 4"	203 dpi / 4"	203 dpi / 4"
Print Method		DT/TT	DT/TT	DT/TT	DT/TT	DT/TT
Max Print Speed (ips)		8	6	6	6	6
Max Print Width		4.13	4.25	4.25	4.25	4.09
Media Roll Diameter (inch) O.D.		8	8	8	5.5	8
Media Thickness (mm)		0.0635~0.254	0.076~0.25	0.076~0.25	0.06-0.19	0.076~0.25
Ribbon Max Length (M)		450	450	450	450	450
Dimension (in) LxWxH		17X10.1X10.3	16.9X10.2X10.9	15.9X10.2X10.8	13X9.8X9.7	17x9.5x10.9
Weight (kg)		13.0	10.9	10.8	7.5	9.1
Connectivity	USB	Standard	Standard	Standard	Standard	Standard
	USB Host	*2	*1	*1	*1	NO
	Serial RS-232	Standard	Standard	Standard	Standard	Standard
	LAN	Standard	Standard	Standard	Standard	Standard
	WLAN	Optional	NO	Optional	Optional	Optional
	Parallel	Optional	NO	Optional	NO	Optional
Print command Languages	EPL	V	NO	V	V	V
	ZPLII	V	V	V	V	V
	DPL	V	NO	V	V	NO
Cutter		Optional	Optional	Optional	Optional	Optional
Peeler		Optional	Optional	Optional	Optional	Optional
Rewinder internally		Optional	NO	Optional	Optional	Optional
GPIO		Optional	NO	NO	NO	NO